

# EMO08

Wall-mount air conditioners for outdoor applications

## COOLING CAPACITY

## 820 W



### Accessories


Pack of 5 fabric air filters	AAEFP10
Pack of 1 metal air filter	AAEFM10
External stainless-steel framework	
Coating in non-standard colour	
48VDC evaporator fan	
Anti-tamper screw kit	
High temperature alarm	
Pressure alarms (low, high)	

Features	UoM	EMO08BM1B	EMO08CM1B	EMO08GM1B
Cooling capacity EN14511 - A35A35	W	820	820	820
Cooling capacity EN14511 - A35A50	W	680	680	680
Power supply	V - Hz	230 1~ 50-60	115 1~ 50-60	400/440 2~ 50-60
Width	mm	363	363	363
Height	mm	895	895	895
Depth	mm	239	239+42***	239+58***
Max current	A	2.6	5.3	1.7
Inrush current	A	10.8	21.5	6.1
T Fuse	A	6	10	6
Power draw EN14511 - A35A35	W	410	420	420
Power draw EN14511 - A35A50	W	490	500	500
Operating cycle	-	100%	100%	100%
Electrical connection	-	4-pin plug	4-pin plug	4-pin plug
R134a Refrigerant	kg	0.28	0.28	0.28
Max refrigeration circuit pressure	bar	25	25	25
External air fan capacity	m <sup>3</sup> /h	570	570	570
Cabinet air fan capacity	m <sup>3</sup> /h	330	330	330
Internal temperature range	°C	+20 - +46	+20 - +46	+20 - +46
Temperature regulation	-	Electromechanical thermostat, factory set to 35°C		
External temperature range	°C	-20 - +55**	-20 - +50	-20 - +50
EN60529 ingress protection - cabinet side	-	IP55	IP55	IP55
EN60529 ingress protection - ambient side	-	IP34*	IP34*	IP34*
Noise level	dB (A)	65	65	65
Weight	kg	27	28	28
Colour	-	RAL 7035 embossed effect		
Conformity	-	CE	CE	CE

\*\*\* Due to external autotransformer dimensions \*\* 50 °C at 60 Hz

\* IP54 rated exterior electrical connections

## Performance



## Dimensions

