

# ACCESSORIES

## LED LIGHT



Features	UoM	AALGT10
Power supply	V - Hz	100-240 V AC, 50/60Hz (min. 90 V AC, max. 265 V AC)
Power draw	W	Max. 5
Luminous flux	Lm	290 Lm at 120° (corresponding to 870 Lm at 360° or 75W for an incandescent bulb)
Light bulb	-	LED, angle of irradiation 120°
Lifetime	h	60,000 h at +20°C (+68 °F)
Connection	-	Two-pin locking plug AC: max. 2,5 A/240 V AC, colour: white
Fastening	-	Magnetic fastening
Housing	-	Plastic, transparent
Dimensions	mm	351x34x32
Weight	g	200
Ambient operating temperature	°C - °F	-30°C - +60°C (-22°F - +140°F)
Ambient storage temperature	°C - °F	-40°C - +85°C (-40°F - +185°F)
Ambient operating/ storage humidity	%RH	max. 90% RH (non-condensing)
Protection class/ IP	rating	IP20/II (double insulated)

### AALGT10


#### LED light with magnetic fastening

The AALGT10 range of lights can be used in all types of cabinets or panels, even where space is extremely limited. The magnetic fastening, the integrated power supply and the locking input and output plugs make installation quick, flexible and safe. Up to 10 lights can be connected in series.

LED technology guarantees a very long lamp lifetime.



**Female plug**  
For power supply cable.



**Male plug**  
Only for connecting multiple lights in series (max 10).

LED light  
**AALGT10**

